

Equipment spec

Model:

SL32E Electric Scissor Lift

Category:

10m/32ft platform height, standard

Working height: 11.75m

Max height: 9.75m

Width: 1.23m

Lifting capacity: 317kg

Weight: 2,302kg

Power: Battery

Standard features

- Drivable at full height with roll out deck fully extended
- Crossover symmetrical 4WD
- 1.52 m roll out extension deck
- 16hp AC electric motor with motor controller
- 48V 250Ah battery pack
- Low voltage battery protection
- Multiple wet disc spring applied, hydraulic release (SAHR) brakes
- AC power to platform
- 45% Gradeability
- Foam filled grip lug nonmarking tyres
- Tilt alarm with drive & lift cut-out
- Lanyard attachment points
- Overload sensing system
- Lowering warning system
- Scissor guard



Model:

SL32E Electric Scissor Lift

Category:

10m/32ft platform height, standard

Dimensions

A	Work Height	11.75 m
B	Raised Platform Height	9.75 m
C	Lowered Platform Height	1.23 m
D	Overall Width	1.17 m
E	Overall Length	2.31 m
F	Stowed Height (Rails Up)	2.24 m
G	Stowed Height (Rails Down)	1.99 m
H	Platform Width (Inside Dimension)	1.07 m
I	Platform Length (Inside Dimension)	2.13 m

Specifications

Extension Deck (Roll Out)	1.22 m
Ground Clearance (Stowed)	8.89 cm
Ground Clearance (Raised)	1.91 cm
Wheelbase	1.75 m
Weight	2,302 kg
Gradeability	25%
Turning Radius (Inside)	1.21 m
Turning Radius (Outside)	2.37 m
Lift Time (With Rated Load)	59 sec
Lower time (With Rated Load)	49 sec
Drive Speed (Stowed)	3.2 km/h
Drive Speed (Raised)	1.1 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	317 kg
Distributed Capacity (Main Platform)	204 kg
Distributed Capacity (Extension Deck)	113 kg
Local Floor Load (With Rated Load)	1538 kPa
Overall Floor Load (With Rated Load)	10 kPa

**Special features**

- Operator horn
- Hinged railing system
- Forklift pockets and tie down/lift lugs