

Equipment spec

Model: SL40E - Scissor Lift

Category: 12m – 40ft, Electric

Working height: 13.80m

Max height: 11.80m

Width: 1.19m

Lifting capacity: 350kg

Weight: 2,985kg

Power: Battery



Standard features

- Drivable at full height
- Variable speed, front wheel hydraulic drive
- DC Motor controller
- Half height hinged gate
- Dual holding brakes
- Proportional controls for drive & lift functions
- 3' (0.9 m) Roll out extension deck
- 24V DC power source
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, nonmarkin tires
- Pothole protection system
- 110V AC outlet on platform with GFI
- 28 mph wind rating (12.5m/sec)
- Tilt alarm with drive & lift cutout
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Hinged railing system
- Forklift pockets and tie down/lift lugs
- Relay based control system
- Color coded and numbered wiring system
- Telematics ready

Model:

SL40E - Scissor Lift

Category:

12m – 40ft, Electric

Dimensions		
Α	Work Height	13.80 m
В	Raised Platform Height	11.80 m
C	Lowered Platform Height	1.37 m
D	Overall Width	1.19 m
Е	Overall Length (Platform Retracted)	2.40 m
F	Stowed Height (Rails Up)	2.48 m
G	Stowed Height (Rails Down)	2.21 m
Н	Platform Width (Inside Railing)	1.06 m
I	Platform Inside Length (Retracted)	2.19 m

Specifications	
Extension Deck	0.90 m
Ground Clearance	8.10 cm
Wheelbase	1.90 cm
Weight	1.85 m
Gradeability	2985 kg
Turning Radius (Inside)	25%
Turning Radius (Outside)	0.54 m
Lift Time (With Rated Load)	2.58 m
Lower time (With Rated Load)	71 sec
Drive Speed (Stowed)	41 sec
Drive Speed (Raised)	3.2 km/h
Maximum Drive Height	1.0 km/h
Capacity (Overall)	Full Height
Local Floor Load (With Rated Load)	350 kg
Overall Floor Load (With Rated Load)	3/0
Maximum # of Persons (indoor/out-door)	Solid, N/M
Tyre Type	16 x 5 x 12
Tyre Size	10 x 16.5



Special features

- Platrom work lights
- Hydraulic generator
- Hydraulic water pump

